

# ANPx101


highest stability, open loop, linear, horizontal stepper positioner

## Technical Specifications


<b>Technology</b>			<b>Compatibility with Electronics</b>		
travel mechanism	inertial piezo drive		ANC300 piezo positioning controller	all versions	
			ANC350 piezo positioning controller	all versions	
<b>Size and Dimensions</b>			<b>Working Conditions</b>		
footprint; height	24 x 24; 11 mm		mounting orientation	axis horizontal	
maximum size	24 x 29; 11 mm		magnetic field range	0 .. 31 T	
weight	20 g		temperature range (/RT, /HV, /UHV)	0 .. 100 °C	
			temperature range (/LT, /LT/HV, /LT/UHV)	10 mK .. 373 K	
			max. bake out temperature (/UHV, /LT/UHV)	150 °C	
<b>Coarse Positioning Mode @ 300 K @ 4 K</b>			minimum pressure (/RT, /LT)	1E-4 mbar	
input voltage range	0 .. 60 V	0 .. 60 V	minimum pressure (/HV, /LT/HV)	1E-8 mbar	
typical actuator capacitance	1.05 µF	0.15 µF	minimum pressure (/UHV, /LT/UHV)	5E-11 mbar	
travel range (step mode)	5 mm	5 mm	<b>Accuracy of Movement</b>		
typical minimum step size	0.05 µm	10 nm	repeatability of step sizes	typically 5 % over full range	
maximum drive velocity	≈ 3 mm/s		forward / backward step asymmetry	typically 5 %	
<b>Fine Positioning Mode @ 300 K @ 4 K</b>			<b>Connectors and Feedthroughs /RT, /LT Versions all /HV, /UHV Versions</b>		
input voltage range	0 .. 100 V	0 .. 150 V	connector type	2-pole pin plug, ø 0.5 mm, d = 2 mm, integrated connector	2-pole pin plug (PEEK), ø 0.5 mm, d = 2 mm, 30 cm cable with connector
fine positioning range	0 .. 5 µm	0 .. 0.8 µm	electrical feedthrough solution	VFT/LT	VFT/HV, VFT/UHV
fine positioning resolution	sub-nm	sub-nm			
<b>Materials (non-magnetic)</b>					
positioner body	titanium (other materials on request)				
actuator	PZT ceramics				
connecting wires	insulated twisted pair, copper				
<b>Load mounting orientation: axis horizontal (@ 300 K)</b>					
maximum load	1 N (100 g)				
maximum static force along the axis	4 N				
maximum dynamic force along the axis	2 N				
<b>Mounting</b>					
from the top	2 through holes dia 2.2 mm, cntrbr. f. M2				
from the bottom	2 threads M2.5 x 6 mm				
load on top	6 threads M2 x 2.8 mm				
<b>Article Numbers</b>					
/RT Version	1001317				
/HV Version	1001313				
/UHV Version	1001314				
/LT Version	1001285				
/LT/HV Version	1001316				
/LT/UHV Version	1001315				
	1001315				

## Technical Drawings


top view




bottom view



3D view



inner position



outer position

