AMC100

1013508

Technical Specifications

Modes of Operation	
open loop positioning	stepping signals for ECS positioners
closed loop positioning	closed loop control for ECS/NUM positioners
remote operation	Ethernet Port and USB (with adapter)
Size and Dimensions	
chassis	22 x 22 x 4.5 cm^3
weight	2 kg
Controller Hardware	
power supply	100/115/230V, 50 .. 60 Hz
connector	IEC inlet
connection cable (ELE - POS)	1 per axis, length: 2m
Software Drivers	
Windows, Linux	Stand-alone application for Windows XP™, 7™, 8™, 10™
	DLL, LabVIEW™, JSON
Output Signals	
output connectors	26-Pin SubD connector
output voltage range	stepping : 0 .. 45 V; fine positioning : 0..45 VDC
frequency range	stepping : 0 .. 5 kHz (1 axis); stepping : 0 .. 2 kHz (3 axes simultaneously)
output current	stepping : max > 16 A peak
maximum capacitance load	2 µF
output noise	< 5 mVpp (500 kHz bandwidth)
resolution of signal generation	680 µV (16 bit)
Trigger Signals	
trigger level definition	LVDS, LVTTL
input trigger	1 per axis
trigger interface	GPIO - port
Features and Upgrades	
/PRO feature	enhanced functionalities and control for closed loop operation
/IO feature	realtime interfacing with external signals (through GPIO port)
/RC remote control feature	wireless control of nanopositioners
AMC/IDS closed loop feature	interferometric position control using attocube`s IDS3010
Rotation Compensation feature	Feed-forward runout compensation of a rotator by two xy-stages

All rights, including rights created by patent grant or registration of a utility model or design as well as rights of technical modifications are reserved. Delivery subject to availability. Designations may be trademarks, the use of which by third parties for their own purposes may violate the rights of the trademark owners. © attocube systems GmbH