

# ANPxy312/RES/LT - linear xy-nanopositionierer

1019578

## Technical Specifications

<b>Size and Dimensions</b>	
footprint; height	34 mm x 34 mm; 18 mm
maximum installation space	40 mm x 40 mm; 18 mm
weight	64 g
<b>Materials</b>	
positioner body	titanium
actuator	PZT ceramics
connecting wires	insulated twisted pair, copper
<b>Coarse Positioning Mode</b>	
travel range (step mode)	6 mm x 6 mm
maximum drive velocity @ 300 K	~ 3 mm/s
input voltage range	0 - 100 V
<b>Fine Positioning Mode</b>	
fine linear positioning range @ 300 K	5 $\mu$ m
fine linear positioning range @ 4 K	0.8 $\mu$ m
fine positioning resolution	sub-nm
input DC voltage range @ 300 K	0 - 100 V
input DC voltage range @ 4 K	0 - 150 V
<b>Position Encoder</b>	
readout mechanism	resistive sensor
sensor resolution	~ 200 nm
repeatability	1.2 $\mu$ m (unidirectional)
<b>Load (@ ambient conditions)</b>	
maximum load	2 kg
maximum dynamic force along the axis	7 N
<b>General Specifications</b>	
min. first natural frequency	1900 Hz

