ANPxy312/RES/LT/UHV - linear xy-nanopositionierer

1019582

Technical Specifications

Size and Dimensions	
footprint; height	34 mm x 34 mm; 18 mm
maximum installation space	40 mm x 40 mm; 18 mm
weight	64 g
Materials	
positioner body	titanium
actuator	PZT ceramics
connecting wires	insulated twisted pair, copper
Coarse Positioning Mode	
travel range (step mode)	6 mm x 6 mm
maximum drive velocity @ 300 K	~ 3 mm/s
input voltage range	0 - 100 V
Fine Positioning Mode	
fine linear positioning range @ 300 K	5 µm
fine linear positioning range @ 4 K	0.8 µm
fine positioning resolution	sub-nm
input DC voltage range @ 300 K	0 - 100 V
input DC voltage range @ 4 K	0 - 150 V
Position Encoder	
readout mechanism	resistive sensor
sensor resolution	~ 200 nm
repeatability	1..2 µm (unidirectional)
Load (@ ambient conditions)	
maximum load	2 kg
maximum dynamic force along the axis	7 N
General Specifications	
min. first natural frequency	1900 Hz















All rights, including rights created by patent grant or registration of a utility model or design as well as rights of technical modifications are reserved. Delivery subject to availability. Designations may be trademarks, the use of which by third parties for their own purposes may violate the rights of the trademark owners. © attocube systems AG