LT-APO/ULWD/NIR/0.35/xs





Technical Specifications

Optical Data	
clear aperture [mm]	4.7
focal length [mm]	6.71
numerical aperture(NA)	0.35
working distance	12.0 mm
Spectral Performance	
AR coating (> 80% trasnmission) [nm]	400 1000
apochromatic range (df < +/- delta) [nm]	670 1105
Compatibility	
environment	high magnetic fields
	low temperature
	ultra-high vacuum
compatible setups	AFM/CFM/cust
	attoDRY800
	CFM I/cust
Size and Dimensions	
length	50.35 mm
weight	approx. 50 g



 $\delta f: chromatic focal shift, \Delta = n^{\star} \ \lambda_{ref} \ / \ (2^{\star}NA^2): depth of focus, n: refractive index, \lambda_{ref}: wavelength used to define focal plane with max. \ \Delta f: chromatic focal shift, \Delta = n^{\star} \ \lambda_{ref} \ / \ (2^{\star}NA^2): depth of focus, n: refractive index, \lambda_{ref}: wavelength used to define focal plane with max. \ \Delta f: chromatic focal shift, \Delta = n^{\star} \ \lambda_{ref} \ / \ (2^{\star}NA^2): depth of focus, n: refractive index, \lambda_{ref}: wavelength used to define focal plane with max. \ \Delta f: chromatic focal shift, \Delta = n^{\star} \ \lambda_{ref}: (2^{\star}NA^2): depth of focus, n: refractive index, \lambda_{ref}: wavelength used to define focal plane with max. \ \Delta f: chromatic focal shift, \Delta = n^{\star} \ \lambda_{ref}: (2^{\star}NA^2): depth of focus, n: refractive index, \lambda_{ref}: wavelength used to define focal plane with max. \ \Delta f: chromatic focal shift, \Delta = n^{\star} \ \lambda_{ref}: (2^{\star}NA^2): depth of focus, n: refractive index, \lambda_{ref}: wavelength used to define focal plane with max. \ \Delta f: chromatic focal shift, \Delta = n^{\star} \ \lambda_{ref}: (2^{\star}NA^2): depth of focus, n: refractive index, \lambda_{ref}: wavelength used to define focal plane with max. \ \Delta f: chromatic focal shift index \ \Delta f: chromati$





