# Nanonis Mimea

1029003

## Technical Specifications

| | |
|---|---|
| **Size and Dimensions** | |
| chassis | OC4 33 x 28 x 7 cm |
| | SC5 33 x 28 x 7 cm |
| | RC5e 33 x 28 x 21 cm |
| weight | SC5 4.2 kg |
| | RC5e 8 kg |
| | OC4 3.7 kg |
| **Controller Hardware** | |
| power supply | 100-240 V ±10%, 50/60 Hz ±5%, Fuses 200 V T4AH (RC5e), 100/120/230 V ±10%, 50/60 Hz ±5%, Fuses 250 V 2AT (SC5, OC4) |
| power consumption | RC5e 85 W typ., 220W max. |
| | SC5 35 W typ., 60W max. |
| | OC4 11 W typ., 25W max. |
| connector | IEC inlet (3x) |
| **RC5e computing and connectivity** | |
| real-time processing | NI PXIe-8840 real-time system with Intel Corei5 CPU 2.7 GHz, 4 GB RAM |
| FPGA | NI PXIe-7976 |
| operating system | LabVIEW real-time OS |
| signal interfaces connectivity | 3x SC5 max., 2x SO5 max., 2x OC4 max. Total of max. 6 frontends |
| data transfer to host PC | 1 Gbit/s TCP/IP, 2 kS/s default, up to 20 kS/s, 1 MS/s x 8 channels for data streaming |
| **Output Signals** | |
| frequency range | DC - 40 kHz (SC5), 100 Hz - 5 MHz (OC4) |
| **Detection** | |
| max. measurement bandwidth | DC - 100 kHz (SC5), 100 Hz - 5 MHz (OC4) |
| **Interfaces** | |
| xy scan voltage output | (SC5) 2x BNC -10..+10 V, 20 bit (22 bit with hrDAC), 1 MS/s, 40 kHz, bipolar or unipolar, output limiter, tilt- and drift correction |
| z voltage output | (SC5) 1x -10..+10 V, 20 bit (22 bit with hrDAC), 1 MS/s, 40 kHz, bipolar or unipolar, output limiter, tilt- and drift correction |
| analog ADC inputs | (SC5) 8x BNC -10..+10 V, 18 bit, 1 MS/s, 100 kHz. Can be extended to up to 24 inputs |
| analog DAC outputs | (SC5) 8x BNC -10..+10 V, 20 bit (22 bit with hrDAC), 1 MS/s, 40 kHz (3 outputs used for xy and z). Can be extended to up to 48 outputs |
| high frequency section | (OC4) -10..+10 V, 14 bit, 40 MS/s, 5 MHz ADC and DAC. 16 bit amplitude resolution. Dual Option available. Sync output, TTL-phase-sync output |
| general purpose digital interface | 32 bidirectional 500 kHz TTL I/Os for communication and triggering. Pixel-, line-, frame sync available. 4x input and 4x output 200 MHz TTL I/Os for pulse counting and triggering |
| host computer interface | Ethernet 1 Gbit |
| auxiliary power outlet | +/-15 V (0.3 A) |
| **Resolution** | |
| frame view display modes | up to 7 frame views, 2 line views, generation of additional views with programming interface |
| frame view options | various fitting-, saving (.sxm), and scaling options |
| frame view selection tools | frame position, rotation, scaling, centering, zoom on the fly. Dedicated grid, subgrid and point modes |
| **Scan Generation** | |
| pixel clock [kHz] | 20 kHz for normal scan engine, 1 MHz for fast scan engine |
| resolution | up to 22 bits, depending on oversampling |
| features (scan) | global and local slope compensation |
| scan speed | 100 pm/s - 1.2 mm/s @ 30µm x 30µm (slow scan engine); 30 µm/s - 30 cm/s @ 30µm x 30µm (fast scan engine) |
| frame rate | max. 0.9 Hz @ 100 x 100 pixel (slow scan engine); 50 Hz @ 100 x 100 pixel (fast scan engine) |
| **Signal Architecture** | |
| number of internal signals | 128, access from all software modules and from multiple software modules |
| data rate | 20 KS/s, 1 MS/s, maximum oversampling automatically applied for a given data acquisition rate |
| max. simultaneously acquired signals at 20 kS/s | 24 + 24 for data logging |
| max. simultaneously acquired signals at 1 MS/s | 8 |
| experiments | multiple experiments can be performed in parallel without performance degradation |
| real-time operations | mathematical operations between signals are possible in real-time |
| units | real-world, calibrated SI-units throughout the software |
| data logging | continuous data logging with up to 100 M points per file and up to 24 channels at up to 20 kS/s |
| data display | multiple charts, graphs, oscilloscopes and spectrum analyzer |
| **Sample Positioning** | |
| sensor type | interferometric (IDS) or position triggered scanning |
| closed loop sensor range | 5 mm x 5 mm |
| closed loop scan resolution (steady state, 100 ms sample time) | down to 1 nm (usually limited by noise & vibration levels) |

All rights, including rights created by patent grant or registration of a utility model or design as well as rights of technical modifications are reserved. Delivery subject to availability. Designations may be trademarks, the use of which by third parties for their own purposes may violate the rights of the trademark owners. © attocube systems GmbH

| | |
|---|---|
| **Z Controller** | |
| operation | on the fly switching between controller modes and signals |
| z feedback | digital P/I, anti wind-up |
| z resolution | 18 bit, internal resolution of 32 bit |
| input control signal | any input or internal signal channel |
| features (z controller) | linear, absolute and logarithmic controllers, control on multiple signals (sum, subtraction multiplication, division), invertible polarity, P/I gain in physical units |
| safety | SafeTip functionality for tipcrash protection, triggered by any internal signal. Autorecovery options and autowithfraw including coase motion withdraw for minimzation of data losses and tip damage |
| **Oscillation control** | |
| lock-in signal processing | configurable filters, cut-off frequency between 1 mHz and 50 kHz (time constant), slope between 1. and 8. order |
| demodulators | four independent demodulators for multi-harmonics measurements |
| PLL parameter tuning | PerfectPLL for for automating tuning of PLL parameters according to oscillator parameters |
| resonance curve | frequency sweep with autofit-routine for phase slope, amplitude or phase curve, improves fit precision from UHV to liquid environment |
| Q-control | Q-factor reduction (to 0) or enhancement |
| signal analysis | 40 MS/s oscilloscope and FFT with up to 32k samples, Zoom FFT with filter compensation |
| **Phase Locked Loop (PLL)** | |
| features (PLL) | 2 P/I controllers (4 with dual-OC4) with graphical interface |
| frequency resolution [µHz] | < 1 nHz |
| dual PLL | dual PLL option for multi-excitation schemes. Inlcudes TrueDissipation algorithm and calibration for enhanced dissipation measurements |
| **Q Control** | |
| q feedback type | digital, phase controlled |
| efficiency of Q control | decrease or increase of Q by up to 100% |
| **Spectral Performance** | |
| spectroscopy modes | point/line/grid/subgrid/follow-me spectroscopy (up to 8192 x 8192 pixel for grid and subgrid) |
| spectroscopy type | z-spectroscopy, bias spectroscopy, generic spectroscopy (all GUI parameters), dI/dV with internal Lock-In |
| averaging | 1 us up to 10 s per data point |
| experiments | bias spectroscopy, Z-spectroscopy, generic spectroscopy including time spectroscopy. All modes can be combined with lock-in measurements. |
| data acquisition speed | up to 20 kS/s for bias and Z-spectroscopy, up to 1 MS/s for high-speed generic spectroscopy |
| timing control | start and end settling times, settling time per point, integration time per point. All timing is deterministic. Variable spectroscopy resolution/timing possible |
| autoretract | arbitrary threshold condition, including dual-condition autoretract |
| data display | real-time display for measurements > 2s |
| custom spectroscopy | possible with programming interface or scripting |
| **Second Pass Mode** | |
| second pass mode - working principle | multipass with up to 512 passes with different parameter set |
| second pass mode - parameters | playback recorded pass with parameter offset, wait time, slew rate, speed ratio, alternate setpoint, lock-in on/off |
| application for second pass mode | e.g. MFM, SGM, EFM, KPFM |
| **Lock-In** | |
| number of lock-ins | 1 dual-phase lock-in, up to 8 dual-phase lock-ins possible |
| low frequency Lock-In | 10 mHz - 50 kHz modulation frequency, 120 dB dynamic range, > 100 dB effective dynamic reserve, THD+N better than 90 dB |
| modulation | all DAC channel and most internal signals |
| high frequency Lock-In | 100 Hz - 5 MHz |
| integration time | sync filter and/or low-pass filters (1. to 8. order), cut-off frequency of 75 uHz to 20 kHz (low-frequency Lock-in), 95 mHz to 50 kHz (high-speed Lock-in) |
| lock-in usage | AFM cantilever signal, tuning fork signal etc. (high frequency Lock-In), spectroscopy, vibrational analysis, electrical transport, magnetotransport (low frequency Lock-In) |
| **Optical Data** | |
| oscilloscope | single and dual channel oscilloscopes, arbitrary channels, time base 128 ms to 6.4 s, 2 kHz range, 8192 pixel. Optional 4-channel oscilloscope and spectrum analyzer (time base 32 us to 17 minutes, 1M |
| FFTs | spectrum analyzer, 0-1 kHz range, windowing options, variable averaging. Optional 500 kHz spectrum analyzer |
| **Options and Upgrades** | |
| features (transfer function) | various current preamplifiers, up to 2 MCVA5 differntial voltage preamplifiers. I/O extension to up to 24 inputs and 40 outputs or 16 inputs and 48 outputs. Dual-PLL. RF source up to 40 GHz |
| features (crosslink) | up to 8 lock-ins, up to 8 generic P/I loops, KPFM-Module, Atom-tracking module, real-time scripting module, 4-channel oscilloscope module, Multi-Modulator module, Trigger engine-module |
| **Scan control** | |
| scan engines | 2 independent scan engines, one for standard measurements and spectroscopy (20 kpixel/s), one for high speed or very high resolution scanning (1 Mpixel/s) |
| scan management | on the fly scan pattern control (size, position, rotation), with independent visualization controls (zoom, position,...) All parameters can be adjusted without stopping data acquisition |
| history display | up to 50 acquired images can be pasted to scan display background, background management tool |
| tilt compensation | automatic for full scan frame or user-defined area |
| scan display | up to 7 scan displays |

All rights, including rights created by patent grant or registration of a utility model or design as well as rights of technical modifications are reserved. Delivery subject to availability. Designations may be trademarks, the use of which by third parties for their own purposes may violate the rights of the trademark owners. © attocube systems GmbH

| | |
|---|---|
| multipass mode | records any signal on first pass and plays it back on following passes. Multiple passes with configurable z-offset, bias, scan speed and setpoint settings, independent for forward and backward |
| point and shoot spectroscopy | any spectroscopy measurement, or any custom routine or script can be executed on the fly during scan |
| scangrid spectroscopy | combined scan and grid spectroscopy. Topographic information with scan resolution and user configura |
| spectroscopy experiments | all standard experiments, additionally any routine configured in scripting or programming interface |
| Programming interface | |
| labVIEW Programming interface | library of VIs that allows a flexible implementation of user-defined and automated measurement routines. Full control of the Nanonis SPM controller over the Programming Interface. Direct control of ex |
| generic Programming interface | same functionality as LabVIEW programming interface, compatible with any programming language (Pytho |
| python interface | python interface for the generic programming interface available on pypi.org |
| Simulation mode | |
| installation | simulation mode available with software, no limit in number of installations. Additional standalone STM simulator applciation |
| functionality | simulates a Si(111) surface, allows simulated STM measurements and access to full software fucntionality over programming interfaces |
| scope | training without hardware, testing of programming interface and scripting routines |

All rights, including rights created by patent grant or registration of a utility model or design as well as rights of technical modifications are reserved. Delivery subject to availability. Designations may be trademarks, the use of which by third parties for their own purposes may violate the rights of the trademark owners. © attocube systems GmbH